



CJENOVNIK

gasne instalacije

prateći pribor za
instalatore

ručni plamenici i patrone

prateći pribor za instalatere



PROFESIONALNI PLAMENIK, tip 1062E



- Patrona: KEMAP 581
- Radi i sa patronama 575, 576, 580, 1121F, 1126F46
- Aluminijsko tijelo
- Ergonomska ručka
- Piezo paljenje
- Integrirani regulator tlaka
- Sustav protiv plamena
- Kontinuirana blokada plamena
- Vrlo visoka temperatura plamen
- Dostupan i za CGA 600 cilindar (1062)

VP 86,57 MP 101,30

PLAMENIK, tip 1047SC 7/16"



- Kompaktni plamenik od mesinga
- Može se koristiti s plinskim patronama:
575, 576, 580, 580S, 580SMINI, 1121F, 1126F46
- Podesivi plamen
- Podesivi ulaz zraka za meki plamen
- Plamen visoke temperature

VP 23,76 MP 27,80

PLAMENIK VISOKE UČINKOVITOSTI, tip 1060



- Može se koristiti s plinskim patronama 575, 576, 580, 580S, 580SMINI, 1121F, 1126F46
- Piezo paljenje
- Ergonomska ručka
- Podesiva snaga
- Podesivi ulaz zraka za meki plamen
- Sustav protiv plamena
- Visokotemperaturni plamen

VP 52,05 MP 60,90

KOMPLET SPREMAN ZA UPOTREBU SA PLAMENIKOM 1047SC, tip 1047SET

- Komplet plamenik + 3 patrone 575



VP 45,51 MP 53,25

KOMPLET PLAMENIK SA UKLJUČENOM PLINSKOM PATRONOM 575, tip 820AKIT

K
KEMPER
GROUP



- Može se koristiti s plinskim patronama 575, 576, 1121F,
- Sustav protiv baklje
- Piezo paljenje
- Podesivi plamen
- Ergonomska mekana ručka
- Uvlačiva kuka za vješanje
- Mlaznica od nehrđajućeg čelika
- Visoka temperaturni plamen

VP 59,61 MP 69,75

PATRONA, tip KEMAP 581

K
KEMPER
GROUP



- Kemap plinski uložak 410ml (250g)
- Mješavina visokih performansi sa 50% (propana / butana 50%)
- Sa 7/16" sigurnosnim ventilom sa vanjskim navojem
- Sa sustavom naopako
- Temperatura izgaranja u kisiku: 3.300°

VP 20,54 MP 24,00

PATRONA, tip NOVACET PLUS 580S

K
KEMPER
GROUP



- Novacet plinski uložak, 380 ml (220 g)
- Specijalna mješavina visoke snage zagrijavanja
- Sa 7/16" sigurnosni ventil s vanjskim navojem
- Sa sustavom protiv plamena

VP 12,26 MP 14,35

PATRONA, tip SUPERGAS 575

K
KEMPER
GROUP



- Supergas patrona, 600 ml (330 g)
- Mješavina visokih performansi s 30% propana/butana 70%
- Sa 7/16" sigurnosni ventil s vanjskim navojem
- Otporna na niske temperature

VP 7,86 MP 9,20

DETEKTOR CURENJA PLINA, revelGAS, tip 1726



Detektor curenja plina REVELGAS 1726 Spray 240gr.

- Ekološki prihvatljiv i nezapaljiv
- Idealno za provjeru curenja gasa uz maksimalnu sigurnost

VP 12,82 MP 15,00

TEFLON TRAKA ZA PLIN, proizvođač "FERMIT" Njemačka, tip FRp PTFE



Odobreno od instituta
IGT Sarajevo



FRp traka za brtvljenje navoja (FINE THREAD) je namotana u smjeru kazaljke na satu za desni navoj i suprotno od kazaljke na satu za lijeve navoje od kraja navoja u smjeru kraja cijevi i sa 50% preklapanjem navoja: Na kraju od konca, traka se jednostavno otkine i pritisne. Tokom naknadnog procesa zavrtnja, FRp navojna traka čvrsto leži u pojedinačnim navojima. Traka s navojem namijenjena je za jednokratnu upotrebu. Prepusti ili krajevi trake ne smiju viriti u cijevi.

Neograničen rok trajanja

Temperatura skladištenja od -15°C do 60°C.

Opseg temperature gasa :-20°C do +125°C, pritisak 5 bar

LPG: 20 bar

Gustina: 60 g/m²

Debljina: 0,10 mm

Širina: 12 mm

Dužina: 12 met

Br.za narudžbu: 24010

VP 2,22 MP 2,60

Cijene važe do 31.01.2025 godine

TERRAGAZ BH d.o.o.



TERRAGAZ BH d.o.o.
Ul. Nikole Šopa 5A
71210 Ilidža, Sarajevo

Tel: 033/840-957
Mob: 061/737-990
mail: semsudin.bajic@terragaz.ba

terragaz.ba